

Just For **BOATLIFT MAT** Series —

PONTOON MAT

- 4 Corners
- 4 Short Frame Pieces
- 8 Long Frame Pieces
- 1 14x24 Mat

BOATLIFT MAT XL

- 4 Corners
- 4 Short Frame Pieces
- 6 Long Frame Pieces
- 1 14x19 Mat

BOATLIFT MAT LARGE

- 4 Corners
- 4 Short Frame Pieces
- 4 Long Frame Pieces
- 1 14x14 Mat


JETSKI MAT

- 4 Corners
- 4 Short Frame Pieces
- 2 Long Frame Pieces
- 1 14x9 Mat


*The **BOATLIFT MAT** series is the simplest to assemble. There are no stakes, grids or zip-ties. Once assembled, it's ready to install in your lake.*

DOCK MAT

- 4 Corners
- 4 Straight Frame Pieces
- 1 14x5.8 Mat



Installing the new
DOCK MAT



IMPORTANT — Before placing Boatlift & Pontoon Mat — You Must Do This First

Before installing, you must **check for “holes” in the lake bottom. Walk the area where you intend to place lift.** The bottom will feel uniformly soft — and then literally, you’ll “step in a hole.”

Boat motors blow holes in lake bottoms where boats dock. These areas fill in with very light silt. The bottom appears uniform — but it’s really a void in the lake bed. If boats have moored at your dock for any length of time — **YOU LIKELY HAVE A HOLE.**

Holes are often near the back footpads. **DO NOT SET A FOOTPAD ON A HOLE!**

Like 3 legs on a 4-leg table — one corner is just hanging in space. Over time, it will fail.

Place your mat where the soil is consistent, either ahead of, or behind the void.

DO NOT SET FOOTPAD DIRECTLY ON THE STEEL FRAME. The frame is designed to create lateral tension, not to hold up weight directly.

Place a 16”x16” patio paver under each footpad. Three reasons:

- Begins weight transfer over a larger area — faster.
- Prevents “gluing” of surfaces. Porous pavers won’t “stick” to footpads or material.
- Gives you a guide to place lift in the same spot each year.

Once installed, **raise your boat up only half-way for a day.** This allows time to observe how the hoist settles. If a corner sinks noticeably more than the others, remove boat and place a 24-inch paver under that footpad.



Anytime you notice uneven sinking, get boat off the lift quickly to assess and resolve the issue.

